

Claims

1. A dermatoscope comprising a plurality of light-emitting diodes, which are arranged around optics,  
5 for indirect illumination of an examination area, and a plurality of optical waveguides, each of said optical wave guides being arranged in front of one associated light-emitting diode and having a light input surface which faces said associated  
10 light-emitting diode, said optical waveguides having an outer wall totally reflecting light emitted from said associated light-emitting diode toward said examination area.
- 15 2. The dermatoscope as claimed in claim 1, wherein a lens is arranged on said light input surface of each of said optical waveguides.
- 20 3. The dermatoscope as claimed in claim 1, wherein a polarization filter is arranged between each of said light-emitting diodes and said optical waveguides.
- 25 4. The dermatoscope as claimed in claim 1, wherein selectively switchable shutters are arranged between said light-emitting diodes and said optical waveguides.
- 30 5. The dermatoscope as claimed in of claim 1, wherein said light-emitting diodes can be switched off selectively.
6. The dermatoscope as claimed in of claim 1, wherein said light-emitting diodes emit light at a differ-

ent wavelength individually or in groups, and can be switched on and off individually or in groups.

- 5 7. A dermatoscope comprising a plurality of light-emitting diodes, which are arranged around optics, for indirect illumination of an examination area, and a single conical prism having a basis surface facing said light-emitting diodes, the cone angle of said conical prism being designed such that the  
10 light which is injected into said basis surface from said light-emitting diodes is totally reflected on an outer cone surface of said conical prism.
- 15 8. The dermatoscope as claimed in claim 7, wherein lenses is provided on said basis surface, each of said lenses being arranged opposite to an associated light-emitting diode.
- 20 9. The dermatoscope as claimed in claim 8, wherein said lenses are adhesively bonded onto or are integrally formed with said base surface of said conical prism.
- 25 10. The dermatoscope as claimed in claim 7, wherein a polarization filter is arranged between each of said light-emitting diodes and said conical prism.
- 30 11. The dermatoscope as claimed in claim 7, wherein selectively switchable shutters are arranged between said light-emitting diodes and said conical prism.

12. The dermatoscope as claimed in of claim 7, wherein said light-emitting diodes can be switched off selectively.
- 5 13. The dermatoscope as claimed in of claim 7, wherein said light-emitting diodes emit light at a different wavelength individually or in groups, and can be switched on and off individually or in groups.
- 10 14. The dermatoscope as claimed in claim 7 , wherein said conical prism has an axial central hole.
- 15 15. The dermatoscope as claimed in claim 14, wherein said central hole comprises a surface having a mat finish.
- 20 16. The dermatoscope as claimed in claim 14, wherein a transparent contact plate covering said examination area, is arranged at an distal end of said central hole.
- 25 17. The dermatoscope as claimed in claim 7, wherein a tubular attachment fitted on said conical prism represents one part of a housing or is used as a holder for said prism on a housing of said dermatoscope for reinforcing.
- 30 18. The dermatoscope as claimed in claim 7, wherein holes into which said light-emitting diodes project are provided in said base surface of said conical prism or in a ring adjacent to said base surface.

19. The dermatoscope as claimed in claim 17, wherein a proximal end of said housing is designed such that a camera or additional optics can be plugged onto said housing via an adapter.

5

20. The dermatoscope as claimed in claim 17, wherein said housing is coupled to a camera such that previously adjusted optics cannot be misadjusted even if said housing is rotated with respect to said camera or with respect to additional optics.

10

21. The dermatoscope as claimed in claim 19, wherein said adapter comprises a camera ring which can be mounted on optics of said camera, a spacer with a series of spring elements arranged in the form of a ring, and a slide ring which surrounds the spacer, releases said spring elements in an open position and provides an interlocking connection to said dermatoscope housing in a closed position.

15